



Rec'd PCT/PTO 08 OCT 2004
CB/1684510938



INVESTOR IN PEOPLE

**PRIORITY
DOCUMENT**
SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

REC'D 22 JUL 2003


WIPO PCT

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.



Signed

[Signature]

Dated 13 May 2003

BEST AVAILABLE COPY



1/77
24JUL02 E735442-1.062949
P01/7700 0.00-0217062.9

The Patent Office

Cardiff Road
Newport
South Wales
NP10 8QQ

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

1. Your reference

GB 0208488.7 ?

2. Patent application number

(The Patent Office will fill in this part)

GB 0208488.7

23 JUL 2002

0217062.9

3. Full name, address and postcode of the or of each applicant (underline all surnames)

TIMOTHY RICHARD MARRY DAVIES 08362 444 001

Patents ADP number (if you know it)

80 RICHMOND WAY

If the applicant is a corporate body, give the country/state of its incorporation

LONDON W14 0AR

4. Title of the invention

Demountable Framing System

5. Name of your agent (if you have one)

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

Patents ADP number (if you know it)

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number
(if you know it)

Date of filing
(day / month / year)

Britain

GB0208488.7

12.04.02

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

No

a) any applicant named in part 3 is not an inventor, or

b) there is an inventor who is not named as an applicant, or

c) any named applicant is a corporate body.

See note (d))

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form.
Do not count copies of the same document

Continuation sheets of this form

Description 5
~~Description~~ & key to drawings 2 Photo 1
Claim(s) 0
Abstract 1
Drawing(s) 10 + 10 *JK*

10. If you are also filing any of the following, state how many against each item.

Priority documents ☐
Translations of priority documents ☐
Statement of inventorship and right to grant of a patent (Patents Form 7/77) ☐
Request for preliminary examination and search (Patents Form 9/77) ☐
Request for substantive examination (Patents Form 10/77) ☐
Any other documents (please specify) ☒ KEY TO DRAWINGS AND 1 PHOTO

11. I/We request the grant of a patent on the basis of this application.

Signature

Date

TR Pamy Davies 23.7.02

12. Name and daytime telephone number of person to contact in the United Kingdom

Richard Pamy Davies
0207 602 7560

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes', Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

DEMOUNTABLE FRAMING SYSTEM

• OUTLINE DESCRIPTION

This invention comprises a framing system for securely placing displayed material behind a (display) a generally rectangular screen and providing a means of hanging the ensemble on a wall or presenting on a horizontal surface. The system is fully "demountable".

• BACKGROUND

Most frames are made of flange elements assembled with fixings to enclose the screen and displayed material. Known "clip frames" replace the flanges with clips. A recent patent, US Patent No 6282828 makes the entire frame into a clip mechanism, mainly for table-top use. As with the two latter systems the proposed invention is intended to be inexpensive, being suitable for flat-packing, self-assembly, and capable of being made from inexpensive materials. It can be used to display photos prints certificates etc, as well as mirrors, clocks or electronic displays. It is intended that the displayed material be smaller than the display screen leaving a transparent margin exposing the structural system, and so allowing flexibility of size.

Other features of the invention:

An optional incorporation of a backing sheet/panel, smaller than the display screen or capable of applying extra pressure (by flexing between its supports) onto the displayed material.

The displayed material can be easily exchanged.

The decorative appearance can also be based on a demountable decorative sheath.

The system can accommodate wall-hanging, (parallel to the wall), table top presentation, or multiples.

The entire ensemble can be dismantled and re-assembled without undoing tool aided fixings, or adhesives.

DESCRIPTION OF INVENTION

A demountable scaffold and framing structure capable of supporting the necessary functional elements to operate as a display frame: the prime task is to support a generally rectangular planar element or "display screen"; but the invention is a structural system with potentially wider applications.

As the minimum necessary functional elements were met by my earlier patent application which also featured a hoop (integral to the rear diagonal elements) attached to the corners of the display screen as a basis for a functional support structure, GB 0208488.7, of 12th April 2002, priority is claimed from that date.

Notional version. (Fig 1a,1b.)

A demountable scaffold structure such that one pair of parallel rods is held in place with another pair of rods at 90 degrees or 45 degrees to the first pair of rods by four rigid hoops whose internal diameter is gauged to accommodate two such rods or two such rods and intermediate planar element(s). The construction is stable except that the hoops can rotate to a position where they do not hold the elements.

Version1 (Fig 2a, 2b, 2c, 2d, 2e, 2f.)

As the rods have been slid into position their extended ends can be used to securely sandwich a framing element located within the bearing area under the rod ends and dimensioned to fit the planar element and/or the limit defined by the hoops; the hoops are thus held in position by the framing element.

Furthermore, since the sliding action of the rods is easier in a direction at 90 degrees to the hoops as their effective aperture size is greater when not reduced by the thickness of the hoops impacting at 45 degrees; (optionally) flexing the rods into position thus results in a spring locking mechanism, so that orthogonal rods will not simply slide out and so reducing the necessary bearing.

Version 2 (Fig 3a,3b, 3c, 3d.)

However, if one pair of rods is attached to the framing element, by sliding into holes in said framing element then the frame element can be curved away from the bearing points to make a free standing, or decorative structure. Curving of the frame elements, partly caused by the angled penetration of the rods, can be augmented by elasticated hoops located to span vertically between the extended ends of the diagonal rods on the rear. It is important that the hoops are also supported on the front by rods locked into them, since they are only partially supported at the rear. The overall effect is thus concave.

Version 3 (Fig 4a, 4b.)

As an alternative to the locking action of the front rods: a custom hoop can be designed in the form of a cone (with normal base and located as usual) so that resistance offered by the rear of the cone against the framing

ment will prevent it from becoming dysfunctional, (by rotating about its diameter.) It can also be customised to incorporate the rods located in it, if made of resilient plastic material. The form is otherwise similar to Version 2.

Version 4 (Fig 5a, 5b, 5c 5d.)

The role of the front rods can be taken by the framing element being in a forward position to support the critical side of the hoop, providing again that the rear rods are located in holes in the framing element (or otherwise affixed.) The overall effect is thus convex.

Version 5 (Fig 6.)

It is possible to dispense with both rods if the hoops are self-supporting by being dynamically loaded as holes in folded back flaps from a framing element of resilient material. These may be vulnerable and can be supported by other elements as before.

Version (Fig 7.)

However, if the hoops are not used both front and rear rods are sufficient to block forward and backward movement of the planar element, and still assuming a planar element of equal dimensions to the frame aperture, it cannot slide horizontally and vertically because these directions are blocked by the frame element as before. Even if the frame element is curved to become self-supporting (and the dimensional constraints being maintained in elevation) a minimal but effective bearing will be maintained in the corner. Thus it is only in the case where, only one set of rods is used, and the planar element must therefore be larger than the effective frame aperture so using the flanges of the frame element as restraining rods, that corresponds in an obvious way to the version described in US Patent No 6282828, claim 8, wherein the planar element is constrained by slots. The second pair of rods, in the present invention, ensures that curvature, or a stressed flat form, is maintained by the scaffold and not the planar element, interacting with the the frame element.

In terms of the structures meeting the requirements of display frames:

- the planar element 2, should be generally rectangular and generally transparent to function as a display screen,
- a backing sheet 7, can be provided either the full size of the display screen, also held in the hoops or smaller, supported by rear rods, and if attached onto said rods by means of holes in the backing sheet then it can also apply dynamic pressure to the displayed material.
- a decorative sheath 11, can be placed on and folded around the frame

Element 1, such that its folds are held on by the scaffold rods 4,5.

- a hanging hole 10 can be provided in the upper flange and in Version 2 would be concealed within the naturally occurring gap behind the decorative sheath, and the same applies for a hole or tongue in the bottom flange to take one end of a tubular "L" shaped strut for table-top use. This strut can be a trimmed drinking straw, also adapted at the other end, to engage the cleft between the rear rods.

Extras:

- Being of light weight the invention is suited to adaption by means of suckers attached in holes or in the gap between frame and display screen, facing forwards or back, to mount on appropriate surfaces.
- The system can be extended to make multiples, vertically, horizontally, and in combination.

CONSTRUCTION

- Self-assembly (Version ²~~1~~) can be as follows:

The rear diagonal rods 5, are inserted diagonally into the holes 15, in the backing sheet 7, to form a unit.

The decorative sheath 11, and frame element 1, are placed together. The rod ends are then placed in the corresponding holes 15, in the decorative sheath 11, and frame element 1, with hoops 3, already attached to each one. The flaps 11a, 11b, of the decorative sheath are folded back into place, with the inner flap under the outer flap, and they are held in place by being under the ends of the rear diagonal rods 5. This unit is secured by elasticated elements looped around the vertical pairs of rod ends 18.

The display screen 2, is placed in the frame aperture 16. The hoops 3, are placed on the corners of the display screen 2 where they are partially restrained by the frame element 1. The front rods 4 are located in one hoop by sliding directly towards the hoop and the flexed to meet the second hoop and carefully eased into the hoop in a straight form, in the orthogonal position, (vertically as a matter of preference.)

The displayed material 14, can be slid into place under the backing sheet 7, optionally leaving a transparent margin.

A rear support strut 9, can be attached for table top use, or suckers can be added if required.

Functional tolerance.

All versions can be adapted with elasticated (finished with toggles), part

elasticated or other taut flexible linear elements performing the blocking function normally taken by the rods. Such tautness can be achieved by for instance twisting bands of resilient or flexible material, as featured in the priority application GB 0208488.7. Other means are also possible. Flexibility of rod elements is desirable but not essential. The prototypes use boxwood of square section. (Other sections are possible.)

Tongue extensions of the frame element are also possible adaptive means of securing the hoops by being placed in said hoops. Custom hoops can be provided (as mentioned above) but the norm is to use a standard metal washer form.

The frame element may be of multi-hole construction or lattice structure as a means of providing holes for rods. It can be made of rigid, stiff, or flexible materials, including plastics and foams. The outside edge can be of any configuration. It can also deform in the third dimension providing necessary bearing points have been met.

The decorative sheath can be any sheet material but if corrugated will fold over edges in a restricted way that will also restrict deformations of the frame element in a generally desirable way.

The shape of the cut-out frame aperture is designed to meet the outside edges of the display unit and/or the attached washers.

The proportions and scale of the invention are open variables.

The claims, to be submitted, are designed to maximise the scope of the invention as anticipated in the above descriptions, which, with reference to the drawings, describe specific embodiment(s) of the invention.

ABSTRACT

DEMOUNTABLE FRAMING SYSTEM

A demountable framing system comprising a frame element (1), a display screen (2), display material (14) and optional backing sheet (7), and a means of connecting these wherein:

(as shown in Figures 2a,2b,2c,2d,2e,2f.)

(version 1) the position of the display screen (2), is maintained by hoops (3), on the corners of the display screen (2), into which are located two co-operating pairs of rods (4,5). The hoops are restrained by the frame element (1) which is itself sandwiched between rod ends;

Or *(version 4)*, with only two rods (5) on one (rear) side only, in holes (15) in frame element (1), which then supports the hoop's other (front) half;

Or *(version 3)*,adequately supports a (coned) custom hoop 3b;

Or *(version 2)*, uses front rods(4), but with rear rods(5) located in rear supporting frame element.

The rear rods hold a decorative sheath (11), optionally secured with elastic(18) to provide a firm base for self-assembly and being diagonal, can support a backing panel (7), also able to apply force.

DESCRIPTION OF DRAWINGS

- 1 FIG 1a, 1b
Notional Version
- 2 FIG 2a,2b Version 1: Front views without and with decorative sheath.
- 3 FIG 2c,2d. Version 1: Top view and rear view.
- 4 FIG 2e Version 1: Side view table-top version
FIG 2f Version 1: Adapted for flexible/elastcated rod replacement.
- 5 FIG 3a, 3b. Version 2: Front and rear views.
- 6 FIG 3c,3d. Version 2 : Side cenntal sections of wall and table- top versions.
- 7 FIG 4a. Version 3: Front view.
FIG 4b. Version 3: Section of custom hoop.
- 8 FIG 5a,5b. Version 4: Front and rear views.
- 9 FIG 5c,5d. Version 4 : Plan section and side section.
- 10 FIG 6. Version 5: Front view.
FIG 7. Version 6: Front view.


KEY TO DRAWINGS

- 1 Framing element.
- 2 Display screen.
- 3 Hoops.
- 4 Linear element as front rods.
- 4a Front rods: horizontal.
- 5 Linear element as rear diagonal rods.
- 5a Flexible/elasticated rod replacement.
- 5b Rear rods: vertical.
- 6 Linear element as rear horizontal rods.
- 7 Backing sheet.
- 8 Tongue for attaching tubular support strut.
- 9 Support strut.
- 10 Hanging hole (can also accommodate support strut.)
- 11 Decorative sheath
- 11a Outer fold.
- 11b Inner fold.
- 11c Folded edges.
- 12 Toggle.
- 13 Backing sheet.
- 14 Displayed material
- 15 Holes
- 16 Void.
- 17 Table-top
- 18 Elasticated loop ie "elastic band"
- 19 Wall
- 20 Hanging pin

Photo



Version 2: rear view



Version 2: front view

DESCRIPTION OF DRAWINGS

- 1 FIG 1a, 1b
Notional Version
- 2 FIG 2a,2b Version 1: Front views without and with decorative sheath.
- 3 FIG 2c,2d. Version 1: Top view and rear view.
- 4 FIG 2e Version 1: Side view table-top version
FIG 2f Version 1: Adapted for flexible/elastcated rod replacement.
- 5 FIG 3a, 3b. Version 2: Front and rear views.
- 6 FIG 3c,3d. Version 2 : Side cenntal sections of wall and table- top versions.
- 7 FIG 4a. Version 3: Front view.
FIG 4b. Version 3: Section of custom hoop.
- 8 FIG 5a,5b. Version 4: Front and rear views.
- 9 FIG 5c,5d. Version 4 : Plan section and side section.
- 10 FIG 6. Version 5: Front view.
FIG 7. Version 6: Front view.

KEY TO DRAWINGS

- 1 Framing element.
- 2 Display screen.
- 3 Hoops.
- 4 Linear element as front rods.
- 4a Front rods: horizontal.
- 5 Linear element as rear diagonal rods.
- 5a Flexible/elasticated rod replacement.
- 5b Rear rods: vertical.
- 6 Linear element as rear horizontal rods.
- 7 Backing sheet.
- 8 Tongue for attaching tubular support strut.
- 9 Support strut.
- 10 Hanging hole (can also accommodate support strut.)
- 11 Decorative sheath
- 11a Outer fold.
- 11b Inner fold.
- 11c Folded edges.
- 12 Toggle.
- 13 Backing sheet.
- 14 Displayed material
- 15 Holes
- 16 Void.
- 17 Table-top
- 18 Elasticated loop ie "elastic band"
- 19 Wall
- 20 Hanging pin

Fig 1a
Notional
Version a




Fig 1b
Notional
Version b




FIG 2a Version 1





FIG 2b Version 1



3/10

FIG 2c Version 1




FIG 2d Version 1
rear view

FIG 2e
side view
version 1
table top




FIG 2f
corner
adapted version 1
(flexible linear
element)





FIG 3a

version 2
front view

**FIG 3b**

version 2
rear view




FIG 3c
version 2
wall-hanging
central section





Fig 3 d
version 2
table-top
central section



7/10

FIG4a
version 3
front view





FIG 4b
version 3
custom hoop



8/10

FIG 5a version 4 front view





Fig 5b version 4 rear view



9/10

Fig 5c
version 4
plan section




Fig 5d
side section
version 4
table-top




FIG 6 Version 5







FIG 7 Version 6



Version 2: front view.



Version 2: rear view.



Photo

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.